

Product sheet

Mymesh Gateway

mymesh.nl sales@mymesh.nl

Making buildings smart

Description

The Mymesh Gateway enables communication between the Mymesh network and the compatible commissioning App for iPad.

Technical summary

The Mymesh Gateway uses the Mymesh network protocol to communicate with the Mymesh network and uses the Bluetooth Low Energy protocol to communicate with the iPad.

Product features

- Comes with a rechargeable battery including USB-C power connector
- Commissioning App for iPad available for commissioning of Mymesh devices

Network features

4

- Wireless, stand-alone network that is selforganizing and self-healing
- 2.4GHz communication for reliable data transfer
- Secure by design
- Ultra scalable to > 10,000 devices in one network
- Updates and new functionality can be installed with Over-The-Air updates.
- Cloud interface (API) available to connect with Building Automation Systems, dashboards, user apps and more.

This product sheet is subject to change without notice.



Device Information

| Connections | | Certification | |
|-------------------|---------------------|-----------------|-----------------|
| Power Connector | USB-C - 5V DC 500mA | RED / CE / UKCA | |
| | | | |
| Order information | | Housing | |
| Mymesh Gateway | BLC.2840.001 | LxWxH | 115 x 63 x12 mm |
| | | Material | ABS (UL94HB) |
| | | Colour | White |
| Radio | | | |
| Band | 2.4GHz ISM band | | |